

TECHNICAL SPECIFICATIONS (METRIC)

Water volume	Part number	Service pressure	Test pressure	Capacity N ₂	Capacity O ₂	Diameter	Length	Weight	Internal volume	Water weight	Specification	Thread size
<i>l</i>		<i>bar</i>		<i>l</i>	<i>l</i>	<i>mm</i>	<i>mm</i>	<i>kg</i>	<i>l</i>	<i>kg</i>		
-	N004	153	-	103.4	114.1	81	229	0.8	0.7	0.7	DOT-3AL / TC-3ALM	0.750-16UNF-2B
-	N006	153	-	150.7	164.5	81	299	1.0	1.0	1.0	DOT-3AL / TC-3ALM	0.750-16UNF-2B
-	N007	139	-	193.7	209.6	111	233	1.4	1.4	1.4	DOT-3AL / TC-3ALM	0.750-16UNF-2B
-	N009	139	-	229.4	248.4	111	270	1.7	1.7	1.7	DOT-3AL / TC-3ALM	0.750-16UNF-2B
-	N011	139	-	307.3	332.5	111	351	2.1	2.3	2.3	DOT-3AL / TC-3ALM	0.750-16UNF-2B
-	N022	153	-	591.9	647.1	133	435	3.9	4.0	4.0	DOT-3AL / TC-3ALM	0.750-16UNF-2B, 0.750-14 NGT, 1.125-12UNF-2B
-	N033	153	-	875.1	954.4	175	397	6.5	5.9	5.9	DOT-3AL / TC-3ALM	0.750-16UNF-2B, 0.750-14 NGT, 1.125-12UNF-2B
-	N042	153	-	1252.0	1365.6	133	841	7.2	8.4	8.4	DOT-3AL / TC-3ALM	0.750-16UNF-2B, 0.750-14 NGT, 1.125-12UNF-2B
-	N047	147	-	1342.4	1461.3	175	584	9.1	9.4	9.4	DOT-3AL / TC-3ALM	1.125-12UNF-2B
-	N060	153	-	1580.0	1723.6	184	597	10.2	10.7	10.6	DOT-3AL / TC-3ALM	0.750-14 NGT, 1.125-12UNF-2B, M25 x 2
-	N088	153	-	2333.6	2545.7	184	835	13.7	15.7	15.7	DOT-3AL / TC-3ALM	0.750-14 NGT, 1.125-12UNF-2B
-	N122	153	-	3165.0	3452.5	203	922	17.9	21.3	21.3	DOT-3AL / TC-3ALM	0.750-14 NGT, 1.125-12UNF-2B
-	N150	139	-	4007.6	4338.3	203	1216	22.0	29.5	29.4	DOT-3AL / TC-3ALM	0.750-14 NGT, 1.125-12UNF-2B
-	N155	124	-	4086.6	4383.4	218	1180	22.9	33.4	33.4	DOT-3AL / TC-3ALM	1.125-12UNF-2B
-	N200	207	-	5048.0	5671.1	218	1046	29.3	26.1	26.0	DOT-3AL / TC-3ALM	0.750-14 NGT, 1.125-12UNF-2B, 25E
-	N265	153	-	6881.8	7506.8	250	1305	38.7	46.4	46.3	DOT-3AL / TC-3ALM	0.750-14 NGT, 1.125-12UNF-2B, 25E
-	N269	153	-	7048.8	7688.9	250	1340	42.0	47.5	47.4	DOT-3AL / TC-3ALM	0.750-14 NGT, 1.125-12UNF-2B, 25E
-	-	-	-	-	-	-	-	-	-	-	-	-
0.5	-	200	300	-	-	70	230	0.7	-	-	99/36/EEC	17E
1.0	-	200	300	-	-	102	240	1.6	-	-	99/36/EEC	17E
2.0	-	200	300	-	-	102	390	2.6	-	-	99/36/EEC	25E
3.0	-	200	300	-	-	111	495	3.7	-	-	99/36/EEC	25E
5.0	-	200	300	-	-	140	525	6.6	-	-	99/36/EEC	25E

Water volume	Part number	Service pressure	Test pressure	Capacity N ₂	Capacity O ₂	Diameter	Length	Weight	Internal volume	Water weight	Specification	Thread size
5.0	-	200	300	-	-	152	460	7.0	-	-	99/36/EEC	25E
10.0	-	200	300	-	-	140	965	11.4	-	-	99/36/EEC	25E
10.0	-	200	300	-	-	176	655	12.8	-	-	99/36/EEC	25E
15.0	-	200	300	-	-	204	735	18.7	-	-	99/36/EEC	25E
20.0	-	200	300	-	-	204	940	23.4	-	-	99/36/EEC	25E
31.5	-	200	300	-	-	229	1150	35.7	-	-	99/36/EEC	25E
40.0	-	200	300	-	-	229	1430	44.3	-	-	99/36/EEC	25E
50.0	-	200	300	-	-	250	1500	56.0	-	-	99/36/EEC	25E

i INFO

Specifications subject to change.

 TECHNICAL SPECIFICATIONS (IMPERIAL)



 INFO